



Streamlining Meter Data Analytics

Liu, Xiufeng; Nielsen, Per Sieverts

Publication date:
2016

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Liu, X., & Nielsen, P. S. (2016). *Streamlining Meter Data Analytics*. Poster session presented at 3rd General Consortium Meeting of Smart Cities project, CITIES, Kgs. Lyngby, Denmark. <http://smart-cities-centre.org/events/consortium-meetings/third-general-consortium-meeting-dtu-may-24th-25th-2016/>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal


If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Smart Electricity Meters

- Record and communicate whole-house electricity consumption (e.g., hourly or every 15 minutes)
- Worldwide deployment expected to reach over 600 million meters in 2016 (according to Berg Insight)
- Hourly measurements enable time-of-use billing which can help reduce peak demand
- Smart meter analytics can lead to improved forecasting, money-saving tips for customers, etc.




System Architecture



Smart Meter Analytics


- Input: hourly whole-house smart meter time series and outdoor temperature
- Output:
 - For each customer: simple visualization, histograms, temperature sensitivity analysis, daily load shapes
 - Across customers: clustering, comparison with neighbourhood

Example 1: Temperature Sensitivity Analysis via Degree-Day Plots



- For climates with a summer and winter
- Step 1: fit piecewise regression lines for 10th, 50th and 90th percentiles of hourly consumption as a function of temperature
- Step 2: obtain base load from 10th percentile regression lines
- Step 3: obtain heating and cooling gradients from the 90th percentile regression lines
- Step 4: obtain heating and cooling setpoints from the 90th percentile regression lines


Example 2: Daily Load Shapes via Time Series Auto-Correlation




- Idea: take whole-house smart meter time series (black) and remove the effect of temperature via time-series autocorrelation with temperature as the exogenous variable (blue)
- Then plot the average consumption at each hour of the day

System Functionalities

- Customer Dashboard
 - Your consumption (blue) vs. neighbourhood average (yellow)
 - Personalized feedback



- Analyst Dashboard
 - Histograms, temperature sensitivity, daily load shapes for all customers
 - Clustering based on load shapes
 - Feedback rule engine



Acknowledgements

This research was supported by the CITIES research project (NO. 1035-00027B) funded by Innovation Fund Denmark.

For More Information

- Liu X, Nielsen P S. Streamlining smart meter data analytics. SDEWES2015.0558, 1-14, 2015
- Liu X, Nielsen P S. A Hybrid ICT-solution for smart meter data analytics. Journal of Energy, 2016.